

# XOLEUM

**5W/30 C3 FULLY SYNTHETIC ENGINE OIL**  
5 LITRE & 20 LITRE

# TECHNICAL DATA

## PRODUCT DESCRIPTION

Xoleum C3 fully synthetic engine oil has been specially formulated to meet the requirements of a Low SAPS (Sulphated Ash, Phosphorus and Sulphur) engine oil. Xoleum C3 is suitable for use in vehicles fitted with exhaust after treatment devices that recommend a lubricant of the grade and specification.

## Recommended for use by Xoleum for the following manufacturer's specifications

- ACEA: C3
- API: SN/CF
- BMW: LL-04
- GM: DEXOS 2
- MB: 229.31, 229.51 & 229.52 VW: 502.00 & 505.00

## Product Benefits

- Fully Synthetic Formulation
- Long Life capabilities
- Protects engine at optimum temperature and performance
- For use with exhaust after treatment devices

## Product Usage

Use as per the engine manufacturers recommendations.

## Directions for Use

Use as per the engine manufacturers recommendations.

## Storage Instructions

Store sealed in a cool, dry place.

## Shelf Life

5 years from date of manufacture.

- Appearance** : Amber liquid
- Odour** : Characteristic
- Specific Gravity** : 0.855 @ 15.6°C (typical)
- Solubility** : Insoluble in water
- Flashpoint** : > 200°C



Size	Part No.	Barcode
5 Litre	XOM105	5012465000001
20 Litre	XOM120	5012465000025

# XOLEUM

**5W/30 C3 FULLY SYNTHETIC ENGINE OIL**  
5 LITRE & 20 LITRE

# TECHNICAL DATA

**Kinematic Viscosity @ 40°C** : 71.28 cSt (typical)

**Kinematic Viscosity @ 100°C** : 12.09 cSt (typical)

**Pour Point** : -42°C

## Safety Precautions

Please see our latest EC Safety Data Sheets for details.

## Transport Classification

Please see our latest EC Safety Data Sheets for details.

*\*The information contained in this leaflet is provided to enable the user to assess the product and should not be taken as a specification. All information provided is given in good faith, we can however not assume liability. It is up to the user to ensure that the information and the product is suitable for the use intended.*