

XOLEUM

5W/30 C2/C3 FULLY SYNTHETIC ENGINE OIL
5 LITRE & 20 LITRE

TECHNICAL DATA

PRODUCT DESCRIPTION

Xoleum C2/C3 is a fully synthetic Low SAPS engine oil which is suitable for use in certain vehicles that have exhaust after treatment devices fitted.

Recommended for use by Xoleum for the following manufacturer's specifications

- ACEA: C3 & C2
- API: SN/CF

Product Benefits

- Fully Synthetic
- Low SAPS
- Suitable for use with exhaust after treatment devices

Product Usage

Use as recommended by the engine manufacturer where this grade and specification of engine oil is required.

Dosage Information

As per the manufacturers recommendations.

Storage Instructions

Store upright and sealed in a cool dry place out of the reach of children.

Shelf Life

5 years from date of manufacture.

Appearance

: Amber liquid

Odour

: Characteristic

Specific Gravity

: 0.845 @ 15.6°C (typical)

Solubility

: Insoluble in water

Flammability

: Non Flammable

Flashpoint

: 220°C

Kinematic Viscosity @ 40°C

: 66.8 cSt (typical)



Size	Part No.	Barcode
5 Litre	XOM305	5012465000063
20 Litre	XOM320	5012465000087

XOLEUM

5W/30 C2/C3 FULLY SYNTHETIC ENGINE OIL
5 LITRE & 20 LITRE

TECHNICAL DATA

Kinematic Viscosity @ 100°C : 11.6 cSt (typical)

Viscosity : 169

Pour Point : -40°C

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

**The information contained in this leaflet is provided to enable the user to assess the product and should not be taken as a specification. All information provided is given in good faith, we can however not assume liability. It is up to the user to ensure that the information and the product is suitable for the use intended.*