# Technical Data Sheet 24/08/2022

Revision 1

# White Grease

## **PRODUCT OVERVIEW**

A scientifically prepared grease formulated to resist heat & water and also protect against corrosion. White Grease can be used on door and boot hinges, most linkages in the engine bay, '0" rings, gears, bearings, springs, sliding shackles & striker plates. Lubricates all hard surfaces, such as plastic, steel & aluminium.

#### **FEATURES AND BENEFITS**

- Lubricates and protects all moving parts
- Resists heat & moisture
- Short term corrosion protection
- For use in the auto & industrial

#### **TYPICAL APPLICATIONS**

Ideal for use on brake linkages, gear, hinges and door latches and across a range of automotive and marine industries.

## **DIRECTIONS FOR USE**

Remove dust and dirt from surfaces.

Shake can well before use.

Spray from 20 - 25 cms / 8 - 10 inches onto area to be lubricated, use extension to access hard to reach areas. Avoid overspray on belts, hand & foot controls.

Remove any excess with a clean lint free cloth.

# **TECHNICAL DATA**

APPEARANCE White/Off white Liquid

ODOUR Paraffinic
pH Not applicable
AUTO-IGNITION TEMP >230°C

FLAMMABILITY Extremely Flammable

PRESSURE 70 PSI (at 25°c)

#### **PACKAGING SPECIFICATIONS**

PRODUCT NUMBER XOMWGR
UNIT SIZE 500ml
CASE SIZE 12

Bar Code 0754590471329 UFI: THJ5-50C1-600N-0C2X

**STORAGE** Store below 50°c, avoid direct

sunlight

# **A1 Motor Stores**

Unit 20 Waterfield Way, Sketchley Meadows Industrial Estate, Hinckley, LE10 3ER

Tel: +44 (0) 1455 637031 www.a1motorstores.com







SHOCK ABSORBER



TIMING BELT



SPARK PLUG



PISTON



