Technical Data Sheet

09/05/2023 Revision 1

Clear Grease

PRODUCT OVERVIEW

Clear Grease is easy to apply, has high load capability and operates across a wide range of temperatures. Continued lubrication helps to reduce friction, repel moisture and extend component life. Colourless formulation is ideal for all applications & locations.

FEATURES AND BENEFITS

- A high quality clear grease aerosol
- Easy to apply
- Easy in situ greasing of bearings, pivots, couplings, linkages and tools
- Repels water, salt and heat resistant

TYPICAL APPLICATIONS

Ideal for high-speed chains – high viscosity prevents throw-off. Protects against corrosion while also offering high water resistance. Viscous, clear, multi-purpose lubricant for applicants where a clear lubricant is desirable.

DIRECTIONS FOR USE

Remove dust and dirt from surfaces.

Shake can well before use. Spray from 20 - 25 cms / 8 - 10 inches onto area to be lubricated, use extension to access hard to reach areas.

Remove any excess with a clean lint free cloth.

TECHNICAL DATA

APPEARANCE Clear Liquid
ODOUR Paraffinic
pH Not applicable

AUTO-IGNITION TEMP >230°C

FLAMMABILITY Extremely Flammable

PRESSURE 70 PSI (at 25°c)

PACKAGING SPECIFICATIONS

PRODUCT NUMBER XOMCLR
UNIT SIZE 500ml
CASE SIZE 12

Bar Code 0754590471312

UFI: WDJS-NONM-W005-AOGR

STORAGE Store below 50°c, avoid direct

sunlight

A1 Motor Stores

Unit 20 Waterfield Way, Sketchley Meadows Industrial Estate, Hinckley, LE10 3ER

Tel: +44 (0) 1455 637031 www.a1motorstores.com









SHOCK ABSORBER



TIMING BELT



SPARK PLUG



PISTON





