

# EGR CLEANER

## PRODUCT OVERVIEW

Provides thorough cleaning of the air intake system, MAF sensor, inlet valves, turbo & EGR system. Strong power jet spray to support cleaning action dissolves gum, lacquer, tar, carbon and varnish. Restores air flow towards the combustion chamber & is easy to use, cleaning takes only 5 mins! Restores engine performance, provides a regular stable idle & eliminates & avoids starting problems. Apply to the air intake manifold, air flow sensor, inlet valves & EGR valve of diesel engines.

## FEATURES AND BENEFITS

- Dissolves gum, lacquer, tar, carbon & deposits
- Restores perfect air flow towards the combustion chamber
- Strong power jet spray to support cleaning action
- Eliminates and avoids starting problems

## DIRECTIONS FOR USE

Start the engine and let it warm up to operating temperature. Install the extension spray tube onto the spray head. With warm engine, open the air filter housing and remove the air filter. Let engine run at idle. Make sure the extension spray tube is directed into the air intake manifold. Spray with short intervals of maximum 1 second each. After each spraying, wait until the original rpm is regained and the engine runs stable. During the spraying, the rpm can go up or down. Diesel knocking can increase. This is due to the change in the air/fuel ratio. Occasionally increase rpm between 1000 and 1500 rpm for several seconds and wait until engine stabilizes before spraying again. Do not accelerate when rpm drops!! When the rpm doesn't increase during spraying, stop the treatment and contact your workshop. Continue until the 500 ml of product in the aerosol is consumed. Let the engine run at idle for 5 minutes. Stop the engine. Replace disassembled parts. Start engine and drive 5 to 10 km, but do not exceed 3000 rpm. Allow engine to idle again for at least one minute before stopping the engine.

## TECHNICAL DATA

APPEARANCE	Clear Liquid
ODOUR	Ketone/Aromatic
pH	Not applicable
Flash point	<0°C
FLAMMABILITY	Extremely Flammable
PRESSURE	70 PSI (at 25°C)

## PACKAGING SPECIFICATIONS

PRODUCT NUMBER	<b>XOMBCS5L</b>
UNIT SIZE	500ml
CASE SIZE	12
Bar Code	0754590471336
UFI:	DJJS-P01E-H004-NPP2
<b>STORAGE</b>	Store below 50°C, avoid direct sunlight



CLEANS

MAF  
SENSOR



INLET  
VALVES



TURBO



EGR



## A1 Motor Stores

Unit 20 Waterfield Way,  
Sketchley Meadows Industrial Estate,  
Hinckley, LE10 3ER  
Tel: +44 (0) 1455 637031  
www.a1motorstores.com